

QUESTIONS & ANSWERS

Kill your exam at first Attempt



LPI

201-450

LPIC-2 Exam 201, Part 1 of 2, version 4.5

<http://killexams.com/exam-detail/201-450>



QUESTION: 156

What is the purpose of a system mount unit?

- A. It is used by the command `systemd-mount` and allows users to mount partitions to mount points of their choice
- B. It is used only to mount network file systems to local mount points. It cannot be used for local media
- C. It is created by the command `systemd-fstab-generator` to integrate entries from `/etc/fstab` into the system boot process
- D. It is used by the command `mount` when using `system` to mount and unmount file systems

Answer: A

QUESTION: 157

In which directory tree are files modified when changing kernel parameters using the command `sysctl`?

- A. `/sys/kernel/`
- B. `/proc/kernel/`
- C. `/proc/sys/`
- D. `/lib/sys/`
- E. `/sys/proc/`

Answer: C

QUESTION: 158

Which command is used to install a GRUB boot loader into the master boot record?

- A. grub-install
- B. grub-mkconfig
- C. grub-install-mbr
- D. grub-glue-mbr
- E. grub-mbr-setup

Answer: A

QUESTION: 159

Which of the following commands restores only those files containing lpi in their name from the archive lpifiles.tar.gz?

- A. tar xvzf lpifiles.tar.gz --wildcards '*lpi*'
- B. tar xvzwf lpifiles.tar.gz '*lpi*'
- C. tar -xvzf lpifiles.tar.gz --deep '*lpi*'
- D. tar -xvzf lpifiles.tar.gz --subdirs '*lpi*'
- E. tar xvzf lpifiles.tar.gz --globbing '*lpi*'

Answer: A

QUESTION: 160

CORRECT TEXT

Which is the main configuration file for the SystemV init process? (Specify the full name of the file, including path.)

Answer: /etc/inittab

QUESTION: 161

What effect does the -f option to the update-rc.d command have on files in the /etc/rcX.d/ and /etc/init.d/ directories?

- A. It will force the removal of the symlinks in /etc/rcX.d/ even when the links are read only
- B. It will remove both the symlinks in /etc/rcX.d/ and the init script in /etc/init.d/
- C. It will remove the init script in /etc/init.d/ and the symlinks in /etc/rcX.d/ and update the package information of installed files

D. It will force the removal of symlinks in `/etc/rcX.d/` even if the corresponding init script still exists in `/etc/init.d/`

Answer: D

For More exams visit <https://killexams.com/vendors-exam-list>



Kill your exam at First Attempt....Guaranteed!